

OIL & DRIVE CLEANER

Thompson's Oil & Drive Cleaner is formulated to remove stubborn oil, grease and petrol stains from concrete, tarmac and stone surfaces. It can also be diluted for general cleaning.



COMPOSITION

A synergistic blend of surface active agents and other ingredients in an aqueous solution.

Physical Properties

Dry Time		1 hour
Coverage	Per L	4m ²
VOC	Minimal	0-0.29%
Odour		Detergent type
Appearance		Yellow liquid
Viscosity		Low
SIZES		1L & 2L

AREAS OF APPLICATION

Suitable for use on concrete, tarmac, stone driveways & garage floors.

PREPARATION

Give the surface a scrub with a stiff bristle brush.

APPLICATION

Removing stubborn stains: Apply the cleaner directly onto oil, grease & petrol stains. Work into the stain with a stiff bristle brush. Leave for 5 minutes on tarmac and 20 minutes on concrete & stone. Clean down the surface with water and a brush.

General Cleaning: Pour 1L of cleaner into a 5L bucket and fill the bucket up with water. Use a stiff bristle brush to clean the whole area. Leave to dry thoroughly.

DRYING TIME

Surfaces should be dry in 1 hour but make sure they are completely dry before applying any protective coatings.

CLEANING OF TOOLS

All equipment should be cleaned immediately after use by rinsing with plenty of water and detergent.

IMPORTANT NOTES

- Always read the instructions carefully before use
- The cleaner may change the colour & appearance of your tarmac drive or pathway
- Always test the cleaner on a small inconspicuous area first before cleaning the whole area
- Take care when cleaning, as surfaces may become slippery when wet
- Avoid spillage onto surrounding vegetation
- Do not allow neat product to enter drains or watercourses
- PROTECT FROM FROST

STORAGE

Ensure container is fully re-sealed after use. Always store and transport in a secure and upright position. Store in frost free conditions. The shelf life of the product in sealed containers is 2 years.

HEALTH AND SAFETY

Follow and observe all warnings and instructions for use shown on pack. Specific health and safety data sheets are available on request.

DISPOSAL

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

LIABILITY

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonsweatherproofing.co.uk

Web: www.thompsonsweatherproofing.co.uk

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants.

DATASHEETS

All Thompson's Datasheets are available on request from our Technical Services