

ONE COAT DAMP SEAL

Thompson's One Coat Damp Seal permanently covers damp, water and other household stains in one coat. It can be applied directly onto damp walls and ceilings.



COMPOSITION

Thompson's One Coat Damp Seal is low odour, solvent based, highly pigmented, acrylic system.

Physical Properties		
Dry Time		4 hour
Coverage	Per L	5m ²
VOC	Very High	>50%
Odour		Low solvent type
Viscosity		Viscous liquid
SIZES		250ml, 750ml, 2.5L

AREAS OF APPLICATION

Interior walls and ceilings.

PREPARATION

It's important to make sure the cause of damp has been rectified before painting, otherwise it'll just come back. Open doors & windows to make sure the room is well ventilated. Remove any wallpaper and flaking paint with a damp cloth. Fill any cracks or holes, if needed. You can apply this onto damp surfaces, just make sure they're not dripping wet.

APPLICATION

Give the tin a really good stir. Apply with a brush or roller. Apply the paint over the affected area, plus about 30cm around it.

COVERAGE

Coverage rates will depend on the texture & type of surface you're coating.

DRYING TIME

Allow to dry for 4 Hours before decorating over. Dry times will vary depending on the texture & type of surface you're coating.

CLEANING OF TOOLS

All equipment should be cleaned immediately after use with white spirit or brush cleaner. Remove as much product as possible from equipment before washing.

IMPORTANT NOTES

- Always read the instructions carefully before use

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition and sunlight. The shelf life of this product in airtight containers is 3 years. To avoid risk of spillage, always store and transport in a secure and upright position.

HEALTH AND SAFETY

Follow and observe all warnings and instructions for use shown on pack. Specific health and safety data sheets are available on request.

DISPOSAL

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

LIABILITY

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonsweatherproofing.co.uk

Web: www.thompsonsweatherproofing.co.uk

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants.

DATASHEETS

All Thompson's Datasheets are available on request from our Technical Services.