

EMERGENCY INSTANT REPAIR

Thompson's Emergency Instant Repair is a specially formulated, sprayable mastic, for emergency repairs to leaking pipes & guttering.



COMPOSITION

Thompson's Emergency Instant Repair is a solution of mineral rubber, asphalt and binder in mixed solvents, packaged in an aerosol.

Physical Properties

Coverage	Per can	0.2m ²
VOC	High	>50%
Appearance	Black viscous liquid	
Odour	Tar like	
SIZES	450g	

AREAS OF APPLICATION

Suitable for use on leaking roof, guttering, pipes & drains.

PREPARATION

Give the surface a scrub with a stiff bristle brush to remove any dust, dirt or algae. Give the area of repair a light sand.

APPLICATION

Give the can a really good shake until you can hear the mixing balls starting to rattle. Continue to shake the tin for a further minute. Mask area to protect from over-spray. Repeat shaking at regular intervals during use. For small cracks & holes : Hold the aerosol 45-60cm away from the area of repair. Spray until the whole area is covered. For larger areas of repair: use the scrim bandage to reinforce the repair. Hold the aerosol 20-25cm away. Apply typically 2-3 coats or as necessary to achieve total and even coverage, leaving 10-15 minutes between each application.

COVERAGE

Coverage is dependant of thickness of the applied coating.

DRYING TIME

Allow to dry for 24 Hours to develop maximum hardness.

CLEAN UP

Hold the can upside down and spray for 3 seconds to clear the nozzle.

IMPORTANT NOTES

- Always read the instructions carefully before use
- Don't apply if it's raining or forecast to rain
- Highly flammable

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition and sunlight. Store upright and carefully reseal partly used containers.

DISPOSAL

Your local authority may have special ways to get rid of waste coatings.

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants.

HEALTH AND SAFETY

Follow and observe all warnings and instructions for use shown on pack. Specific health and safety data sheets are available on request.

LIABILITY

The information in this Product Data sheet is based on technical knowledge and experience, and every care is taken to ensure its accuracy. This information is provided in good faith but without warranty, given ultimate results will depend on a range of factors beyond our control (such as method of application and surface conditions). We can accept no liability for the performance of products arising out of such use. Standard codes of painting practice should be followed.

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonsweatherproofing.co.uk

Web: www.thompsonsweatherproofing.co.uk

DATASHEETS

All Thompson's Datasheets are available on request from our Technical Services.