

EMERGENCY ROOF REPAIR MASTIC

Thompson's Emergency Roof Repair Mastic is a high performance roofing compound which immediately repairs large holes in leaking roofs, even under water .



COMPOSITION

Thompson's Emergency Roof Repair Mastic is a bituminous, mastic based compound, with a high solids content. Additionally it contains specially selected ingredients that repel water.

Physical Properties		
Dry Time		3-4 hours
Full Cure		3-4 Days
Coverage	Per 750ml	0.13m ²
VOC	Medium	8-24.99%
Application Temperature		5°C - 35°C
Temperature Resistance		-40°C - +75°C
Appearance		Paste
Odour		Solvent Type
SIZES		750ml
COLOURS		Black

AREAS OF APPLICATION

Suitable for use on all types of roofing including felt, asphalt, slate & tiles.

PREPARATION

Ensure surfaces are clean from grease, rust, dirt, moss and algae.

If It's Raining

Brush away any ponded water from the area of repair.

If it's dry:

Get rid of any dust or dirt with a stiff bristle brush. Damp down the surface with white spirit.

APPLICATION

Stir thoroughly before use. Use a trowel or pallet knife to work the mastic into the repair. For small cracks & holes: Pack the repair with a Thick layer of the mastic. Make sure you cover the whole area plus about 10cm around it. For larger cracks & voids: Use a scrim bandage into the coating. Complete the repair by covering the whole area, plus about 25cm around it. For the best sealing results a thickness of around 6mm is required.

COVERAGE

Whilst Thompson's Emergency Roof Repair Mastic is not designed to cover large areas, a 750ml tin will treat an area of 0.13 square metres at the prescribed thickness of 6mm.

DRYING TIME

Thompson's Emergency Roof Repair Mastic will provide instant waterproof protection.

It should be left for the recommended 3-4 days to allow solvents contained in the product to evaporate before permanent repairs are carried out. Ideally, this should be completed within one month of initial application.

Dry Times referenced above will be subject to weather conditions.

CLEANING OF TOOLS

Clean tools and equipment immediately after use with white spirit.

IMPORTANT NOTES

- Always read the instructions
- Wear suitable clothing and protective gloves
- Always store and transport in a secure and upright position

STORAGE

Store in a cool, dry, well ventilated place away from heat and sources of ignition. Store upright and carefully reseal partly used containers. The shelf life of Thompson's Emergency Repair Mastic in unopened containers is 2 Years .

HEALTH AND SAFETY

Follow and observe all warnings and instructions for use shown on pack. Specific health and safety data sheets are available on request.

DISPOSAL

Don't empty any left over product into drains or watercourses. Your local authority may have special ways to get rid of waste coatings.

LIABILITY

Whilst these specifications are based on expert technical knowledge and practical experience, we cannot assume responsibility for any work as the ultimate result depends on factors beyond our direct control. Standard codes of painting practice should be followed.

INFORMATION AND SERVICES

Our Technical Services Department will be pleased to offer specific guidance or provide any further information you may require.

Tel: 0114 240 9469

Email: enquiry@thompsonsweatherproofing.co.uk

Web: www.thompsonsweatherproofing.co.uk

SUPPLY

Obtain from DIY outlets, paint suppliers & builders' merchants.

DATASHEETS

All Thompson's Datasheets are available on request from our Technical Services